



Engineered to **Redefine** **High Performance** **Industrial Printing**



GT4e Series

INDUSTRY VERTICALS

- Manufacturing
- Logistics
- Transportation
- Automobile
- Retail
- Government

APPLICATIONS

- Asset Tracking
- Warehouse Management System
- Logistic Tracking
- Retail Labelling
- Laboratory High-Resolution Labelling at 609dpi

RFID-ready ▶

No PC required ▶

Triple-interface connectivity for a truly versatile printing solution ▶

Large LCD display with graphical icons for user-friendly operation ▶

Easy-to-navigate menu options ▶

609dpi high resolution printing ▶



General Specifications

GT4e 

PRINTER MODEL		GT408e	GT412e	GT424e
PRINTING SPECIFICATIONS				
Print Method		Direct Thermal/Thermal Transfer		
Print Resolution		8 dots/mm (203dpi)	12 dots/mm (305dpi)	24 dots/mm (609dpi)
Max Print Speed		300mm/sec (12ips)	300mm/sec (12ips)	150mm/sec (6ips)
Max Print Area		Max (W x P): 104 x 2500mm (4.1" x 98.4")	Max (W x P): 104 x 1500mm (4.1" x 59.1")	Max (W x P): 104 x 400mm (4.1" x 15.7")
MEDIA SPECIFICATIONS				
Sensor Type		Reflective Sensor (for use with pre-printed marks), Adjustable See-Through Sensor (for die-cut labels with gaps)		
Media Thickness		Label thickness (With backing liner): 0.06 to 0.268 mm (0.002" to 0.01")		
Media Size		Width: 22 ~ 128mm (0.87" ~ 5.04"). With paper backing, 25 ~ 131mm (1" ~ 5.16") Pitch: 5 ~ 397mm (0.2" ~ 15.63"). With paper backing, 9 ~ 400mm (0.35" ~ 15.74")		
Media Roll Outer Diameter		Max external diameter 265mm (Paper core size: 1.5", 3", 4")		
Wind Direction		For Face-in and Face-out (Face-out is for linerless labels only)		
CONSUMABLES SPECIFICATIONS				
Ribbon Size	Width	Max: 128mm (5.04")		
	Length	Max: 450m		
	Winding Direction	Face-in and Face-out		
MEMORY/PROCESSING				
Main Memory		Flash-ROM: 6MB		
CPU		32 bit RISC		
COMMUNICATION INTERFACES				
Standard Interface		Plug In Interface Cards: RS-232C, High-speed RS-232C, USB, IEEE 1284, LAN, Centronics, RS-422/485 or Wireless LAN		
Optional		Mini LAN		
External Port		14-pin connector, 25-pin connector		
FONTS/BARCODE SYMBOLOGIES				
Standard Fonts		U, S, M, WB, WL, XU, XS, XM, XB, XL, OUTLINE, OCR-A, OCR-B		
TrueType Fonts		CG Times, CG Triumvirate		
Barcodes	1D Barcode	UPC-A/E, JAN/EAN, CODE 39, CODE 93, CODE 128, UCC/EAN 128, NW-7, Customer Barcode, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, BookLand, POSTNET, RSS-14		
	2D Barcode	QRCode (Chinese QR and Korean QR are individually operated), PDF 417 (Including Micro PDF417), MAXI Code, Data Matrix, Composite Symbology (Compatible with CC-A/B/C by UPC-A/E, JAN/EAN, CODE 39, CODE 128, RSS-14)		
	Character Rotation	0°, 90°, 180°, 270° rotation		
OPERATING & ENVIRONMENTAL				
Power Consumption		Max: 200VA / 200W (Standby: 62VA / 89W)		
Power Supply		Current AC 100 - 240 V		
Dimensions		(W x D x H): 271 x 455 x 305mm (10.67" x 17.9" x 12")		
Weight		Approx. 15kg		
Temperature / Humidity		Usage Environment: 0 ~ 40°C / 30 ~ 80%RH (Non condensing) Storage Environment: -5 ~ 60°C / 30 ~ 90%RH (Non condensing)		
ACCESSORIES & OPTIONS				
Special Options		Cutter, Dispense Unit (with Backing Paper Rewinder), Dispenser, Internal Rewinder, Linerless Kit, RFID Kit, Real Time Clock		
Memory Cartridge		Extended Flash Memory Board (24MB)		

Contact For more information about SATO around the globe, visit www.satoworldwide.com

AMERICAS

10350A Nations Ford Road Charlotte, NC
28273
Tel: (704) 644-1650
Fax: (704) 644-1662
E: satosales@satoamerica.com

ASIA PACIFIC & OCEANIA

438B, Alexandra Road,
#09-01/02, Alexandra Technopark
Singapore 119968
Tel: (65) 6271-5300
Fax: (65) 6273-6011
E: sales@satoasiapacific.com

EUROPE

Lambroekstraat 5A, 1831 Diegem, Belgium
Tel: (32) 2 719 03 90
Fax: (32) 2 719 03 99
E: info@be.satoeurope.com

For sales & general enquiries: sales@satogbs.com